



Features

- Electronic Ballast and Direct Wire compatible
- Workable voltage 90-305V
- Power factor >0.97
- High efficacy up to 139 L/W
- Lamp Life 50,000 hours
- Instant on—200mA current
- Operating temp -25°C - +45°C
-13°F - +113°F
- Case quantity: 25 per box
- UL, RoHS & FCC approved
- D 1.1" L 23.7"
- Safety switch attached to prevent shocking
- Silicone filled to prevent overheating
- Fits standard T8 / T12 sockets
- 7 Year warranty
- Standard white finish at ends
- LM-79 & LM-80 certified
- 120° beam angle
- ANSI surge protection
- Non-dimmable

Applications

- Offices
- Workshops
- Basements
- Task lighting

Ordering Information:

Ex. TD24H-1L-50K-UL



Model

TD24H= 24" High Efficiency Tube

Lumen Package

1L = 900 Lm, 8.8W

CCT

35K = 3500K
40K = 4000K
50K = 5000K

Voltage

UL = 120-277V





Features

- Electronic Ballast and Direct Wire compatible
- Workable voltage 90-305V
- Power factor >0.97
- High efficacy up to 155 L/W
- Lamp Life 50,000 hours
- Instant on—200mA current
- Operating temp -25°C - +45° C / -13°F - +113°F
- Case quantity: 25 per box
- UL, RoHS & FCC approved
- D 1.1" L 23.7"
- Safety switch attached to prevent shocking
- Silicone filled to prevent overheating
- Fits standard T8 / T12 sockets
- 7 Year warranty
- Standard white finish at ends
- LM-79 & LM-80 certified
- 120° beam angle
- ANSI surge protection
- Non-dimmable

Applications

- Offices
- Workshops
- Basements
- Task lighting

Ordering Information:

Ex. TD24U-1L-35K-UL



Model

TD24U = 24" Ultra High Efficiency Tube

Lumen Package

1L = 900 Lm, 6W

CCT

35K = 3500K
40K = 4000K
50K = 5000K

Voltage

UL = 120-277V

