



Features

- Electronic Ballast and Direct Wire compatible
- Workable voltage 90-305V
- Power factor >0.97
- High efficacy up to 111 L/W
- Lamp Life 50,000 hours
- Instant on—200mA current
- Operating temp -25°C - +45°C
-13°F - +113°F
- Case quantity: 25 per box
- UL, DLC, RoHS & FCC approved
- D 1.1" L 23.7"
- Safety switch attached
- Silicone fill on ends
- Fits standard T8 / T12 sockets
- 7 Year warranty
- Standard white finish at ends
- LM-79 & LM-80 certified
- 120° beam angle
- ANSI surge protection
- Non-dimmable

Applications

- Offices
- Workshops
- Basements
- Task lighting

OptiFit With Ballast

Model#	SKU	Lumens	Watts	Color Temp CCT (K)	CRI	R9	Lumens Per Watt	Voltage
50738	TD24H-1L-35K-UL	942.7	8.9	3500	>80	6	105.9	120V
50739	TD24H-1L-40K-UL	944.6	8.9	4000	>80	9	106.1	120V
50740	TD24H-1L-50K-UL	980.9	8.8	5000	>80	6	111.4	120V





Features

- Electronic Ballast and Direct Wire compatible
- Workable voltage 90-305V
- Power factor >0.97
- High efficacy up to 155 L/W
- Lamp Life 50,000 hours
- Instant on—200mA current
- Operating temp -25°C - +45°C /13°F - +113°F
- Case quantity: 25 per box
- UL, DLC, RoHS & FCC approved
- D1.1" L 23.7"
- Fits standard T8 / T12 sockets
- 7 Year warranty
- Standard white finish at ends
- LM-79 & LM-80 certified
- 120° beam angle
- ANSI surge protection
- Non-dimmable

Applications

- Offices
- Workshops
- Basements
- Task lighting

OptiFit With Ballast

Model#	SKU	Lumens	Watts	Color Temp	CRI	R9	Lumens Per	Voltage
50723	TD24U-1L-35K-UL	902.6	8.1	3500	>80	3	111.4	120V
50724	TD24U-1L-40K-UL	943.3	8.2	4000	>80	9	115.0	120V
50727	TD24U-1L-50K-UL	938.8	8.1	5000	>80	2	115.9	120V

