




## Features

- Electronic Ballast Compatible
- Workable voltage 90-305V
- Power factor >0.96
- High efficacy up to 121 L/W
- Lamp Life 50,000 hours
- Operating temp -25°C - +45°C / -13°F - + 113°F
- Instant on—200mA current
- UL, DLC, RoHS & FCC approved
- Replaces F32T8
- Weight: 0.6lbs
- Fits standard T8 / T12 sockets
- 7 year warranty
- D 1.1" x L 47.7"
- Standard white finish at ends
- LM79/80 reports available
- 120° beam angle
- ANSI surge protection
- Non-dimmable

## Applications

- Offices
- Workshops
- Basements
- Task lighting

### Items Stocked in Illinois Warehouse

Model#	SKU	Product	Lumens	Watts	Color Temp	CRI	R9	Lumens Pe Watt	Input Voltage*	IES File
50705	TD48-2L-35K-UL	48" TLED	2052	19.0	3500	>80	10	108	100-277V	
50703	TD48-2L-40K-UL	48" TLED	1896	17.2	4000	>80	17	110	100-277V	
50707	TD48-2L-50K-UL	48" TLED	2111	18.3	5000	>80	5	115	100-277V	





### Features

- Electronic Ballast Compatible or Direct Wire
- Workable voltage 90-305V
- Power factor >0.96
- High efficacy up to 143 L/W
- Lamp Life 50,000 hours
- Operating temp -25°C - +45°C  
-13°F - +113°F
- Instant on—200mA current
- UL, DLC, RoHS & FCC approved
- Replaces F32T8
- Weight: 0.6lbs
- Fits standard T8 / T12 sockets
- 7 Year warranty
- D 1.1" x L 47.7"
- Standard white finish at ends
- LM79/80 reports available
- 120° beam angle
- ANSI surge protection
- Non-dimmable

### Applications

- Offices
- Workshops
- Basements
- Task lighting

### Items Stocked in Illinois Warehouse

Model#	SKU	Product	Lumens	Watts	Color Temp CCT (K)	CRI	R9	Lumens Per Watt	Voltage
50729	TD48H-2L-35K-UL	48" TLED	1839	16.4	3500	>80	6	112	120V
50730	TD48H-2L-40K-UL	48" TLED	1863	16.7	4000	>80	9	111	120V
50731	TD48H-2L-50K-UL	48" TLED	1892	16.5	5000	>80	6	114	120V





### Features

- Electronic Ballast Compatible
- Workable voltage 90-305V
- Power factor >0.96
- High efficacy up to 152 L/W
- Lamp Life 50,000 hours
- Operating temp -25°C - +45°C / -13°F - +113°F
- Instant on—200mA current
- UL, DLC, RoHS & FCC approved
- Replaces F32T8
- Weight: 0.6lbs
- Fits standard T8 / T12 sockets
- 7 year warranty
- D 1.1" x L 47.7"
- Standard white finish at ends
- LM79/80 reports available
- 120° beam angle
- ANSI surge protection
- Non-dimmable

### Applications

- Offices
- Workshops
- Basements
- Task lighting

### Items Stocked in Illinois Warehouse

Model#	SKU	Product	Lumens	Watts	Color Temp CCT (K)	CRI	R9	Lumens Per Watt	Voltage
50725	TD48U-2L-35K-UL	48" TLED	1646	15.3	3500	>80	6	107	120V
50726	TD48U-2L-40K-UL	48" TLED	1704	15.3	4000	>80	6	111	120V
50728	TD48U-2L-50K-UL	48" TLED	1730	15.6	5000	>80	4	110	120V

