



Features

- Electronic Ballast and Direct Wire compatible
- Workable voltage 90-305V
- Power factor >0.96
- 115-121 lumens per watt
- Lamp Life 55,000 hours
- Operating temp -25°C - +45°C
-13°F - +113°F
- Instant on—200mA current
- D 1.1" L 47.7"
- Case quantity: 25 per box
-
-
-
- Fits standard T8 / T12 sockets
- 7 Year warranty
- D 1.1" L 47.7"
- Standard white finish at ends
- LM-79 & LM-80 certified
- 120° beam angle
- ANSI surge protection
- Non-dimmable

Applications

- Offices
- Workshops
- Basements
- Task lighting

Ordering Information:

Ex. TD48-2L-50K-UL



Model

TD48= 48" Tube

Lumen Package

2L = 2000 Lm, 17W

CCT

35K = 3500K

40K = 4000K

50K = 5000K

Voltage

UL = 120-277V





Features

- Electronic Ballast and Direct Wire compatible
- Workable voltage 90-305V
- Power factor >0.96
- High efficacy up to 143 L/W
- Lamp Life 50,000 hours
- Operating temp -25°C - +45°C
-13°F - +113°F
- Instant on—200mA current
- Replaces F32T8
- Case quantity: 25 per box
- Weight: 0.6lbs
- Safety switch attached to prevent shocking
- Silicone filled to prevent overheating
- Fits standard T8 / T12 sockets
- 7 Year warranty
- D 1.1" L 47.7"
- Standard white finish at ends
- LM-79/LM-80 reports available
- 120° beam angle
- ANSI surge protection
- Non-dimmable

Applications

- Offices
- Workshops
- Basements
- Task lighting

Ordering Information:

Ex. TD48H-2L-50K-UL



Model

TD48H= 48" High Efficiency Tube

Lumen Package

2L = 2000 Lm, 15W

CCT

35K = 3500K

40K = 4000K

50K = 5000K

Voltage

UL = 120-277V





ALSET® 48" LED OptiFit Ultra High-Efficiency Tube



Features

- Electronic Ballast and Direct Wire compatible
- Workable voltage 90-305V
- Power factor >0.96
- High efficacy up to 152 L/W
- Lamp Life 50,000 hours
- Operating temp -25°C - +45°C / -13°F - +113°F
- Instant on—200mA current
- UL, DLC RoHS & FFC approved
- Replaces F32T8
- Weight: 0.6lbs
- Safety switch attached to prevent shocking
- Silicone filled to prevent overheating
- Fits standard T8 / T12 sockets
- 7 Year warranty
- D 1.1" L 47.7"
- Standard white finish at ends
- LM-79/LM-80 reports available
- 120° beam angle
- ANSI surge protection
- Non-dimmable

Applications

- Offices
- Workshops
- Basements
- Task lighting

Ordering Information:

Ex. TD48U-2L-50K-UL

	-		-		-	
--	---	--	---	--	---	--

Model

TD48U= 48" Ultra High Efficiency Tube

Lumen Package

2L = 2000 Lm, 13W

CCT

35K = 3500K

40K = 4000K

50K = 5000K

Voltage

UL = 120-277V

