





Features

- Frosted lens to reduce glare
- Rated Life 60,000 hours
- High efficacy at 103-108 lumens per watt
- Available 2700K, 3500K, and 4000K color temperatures
- Lower maintenance costs
- Superior heat management
- Easy installation. Mounting bracket adjusts 5"-6" recessed housing
- Dimensions 7.56" x 2.42" (3.43 aperture)
- Workable voltage 100-135V
- LM79/80 reports available
- Weight: 0.7lbs
- Operating temp -40°C - +45°C / -40°F - +113°F
- Includes E26 Adapter
- Instant on to full brightness
- Dimmable - for compatible dimmer list visit www.ALSETLED.com
- UL, Energy Star, RoHs and FCC certified
- 7 year warranty

Applications

- Bathrooms
- Kitchens
- Basements
- Other damp locations

Items Stocked in Illinois Warehouse

Reference #	Model Number	Lumens	Watts	Color Temp (K)	CRI	Lumens per Watt	Voltage	Wattage Equivalent	IES File
51612	RF6-6L-27K-ST	600	6	2700K	>80	103	120V	65W Incandescent	
51613	RF6-6L-35K-ST	600	6	3500K	>80	103	120V	65W Incandescent	
51614	RF6-10L-27K-ST	1000	9	2700K	>80	106	120V	100W Incandescent	
51615	RF6-10L-35K-ST	1000	9	3500K	>80	106	120V	100W Incandescent	
51616	RF6-14L-27K-ST	1400	13	2700K	>80	108	120V	100W Incandescent	
51617	RF6-14L-35K-ST	1400	13	3500K	>80	108	120V	100W Incandescent	