



Features

- Frosted lens to reduce glare
- Instant on to full brightness
- Rated Life 60,000 hours
- High efficacy at 110 lumens per watt
- Available 3000K and 4000K color temperatures
- Lower maintenance costs
- Superior heat management
- Easy installation. Mounting bracket adjusts to fit 8"-10" recessed housing
- Dimensions 11.2" x 4.92" / 2.87 lbs
- Operating temp -40°C - +45°C
-40°F - +113°F

- Can be used in retrofit applications and new construction
- 0-10V dimming standard
- UL, RoHS and FCC certified
- 7 year warranty
- Workable voltage 90-305V

Applications

- Lobbies
- Atriums
- Retail Stores
- Churches

Items Stocked in Illinois Warehouse

Model Number	Lumens	Watts	Color Temp (K)	CRI	Lumens per Watt	Voltage	Wattage Equivalent	IES Files
RF8-22L-30K-UL	2,200	20	3000K	>80	110	120-277V	42W CFL	↓
RF8-22L-40K-UL	2,200	20	4000K	>80	110	120-277V	42W CFL	
RF8-30L-30K-UL	3,000	27	3000K	>80	110	120-277V	70W CFL	↓
RF8-30L-40K-UL	3,000	27	4000K	>80	110	120-277V	50 W MH	
RF8-40L-30K-UL	4,000	36	3000K	>80	110	120-277V	100W MH	↓
RF8-40L-40K-UL	4,000	36	4000K	>80	110	120-277V	100W MH	

