



## Features

- L70 >60,000 hours at 85°C
- Frosted lens to reduce glare
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy at 116-117 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 3000K, 4000K, and 5000K color temperatures
- Operating temp -40°C - +60°C / -40°F - +140°F
- Dimensions 18.17" x 18.17" x 3.70"
- LM79/80 reports and TM21 data available


- DLC standard under Nuwave model number 53000, 53001
- NSF certified - Splash zone / None-Food
- 0-10 V DC dimming standard
- UL, DLC, RoHs and FCC certified
- 7 year warranty
- Workable Voltage 90-305V
- IP65 Rated for wet locations
- Title 24 compliant
- Unique mounting bracket for simple installation

## Applications

- Indoor / Outdoor lighting
- Gas stations
- Warehouses
- Storage Areas
- Parking garages
- Security
- Entryways & walkways
- Mechanical rooms
- Manufacturing plants
- Loading docks

## Ordering Information:

Ex. CP-11L-50K-UL-AC5



### Model

CP

### Lumen Package

11L = 11,500 lm, 99.5W

### CCT

30K = 3000K  
40K = 4000K  
50K = 5000K

### Voltage

UL = 120-277V

### Options

AC5 = Aircraft Cable (5ft)  
AC10 = Aircraft Cable (10ft)  
CD = 6' Cord  
PS1 = 120V Straight blade plug  
PS2 = 277V Straight blade plug  
PT1 = 120V Twist-Lock plug  
PT2 = 277V Twist-Lock plug

