



## Features

- Two styles available for ease of installation
  - 1 One with a remote driver attached to 3/4" conduit (CPPR)
  - 2 Alternate Option is driver box attached (CPAD)
- Instant on to full brightness
- Wide light distribution
- High efficacy at 116-117 lumens per watt
- Superior heat management yields 60,000 hours life
- Light weight for easy installation
- Lower maintenance costs
- Available 4000k, and 5000k color temperatures
- IP65 Rated for Wet locations
- Operating temp -40°C - +60°C / -40°F - +140°F
- Dimensions: 18.17" x 18.17" x 3.70" (Flat Panel)
- Driver Dimensions: 10" x 6" x 2.25"
- Fits into most 4" hole openings and larger
- 0-10 V DC dimming standard
- UL, DLC, RoHs and FCC (Pending)
- 7 year warranty
- Input voltage 120-277V
- Workable Voltage 90-305V
- Title 24 compliant
- Mounting plate available 23" x 23" Outside dimension

## Applications

- Gas stations
- Security
- Parking garages
- Entryways & walkways

## Ordering Information:

Ex. CPAD-11L-40K-UL

-  -  -

### Model

CPAD=Alternate option( Driver Box Attached)

### Lumen Package

11L = 1550 Lm, 99W

### CCT

40K = 4000K  
50K = 5000K

### Voltage

UL= 120-277V

