



**HLN**



**HLNB**

Model #	Reference #	Lumens	Lumens Per Watt	Color Temp (K)	Watts	HID Equivalent
HLNB-7L-50K-UL	61456	6750	150	5000	45	110W
HLNB-9L-50K-UL	61457	9750	150	5000	65	160W
HLN-10L-50K-UL	61443	10400	130	5000	80	200W
HLN-13L-50K-UL	61444	13000	130	5000	100	250W
HLN-20L-50K-UL	61445	19500	130	5000	150	375W

ex. (HLN) Hazardous Light - (10L) 10,000 Lumens - (50K) 5000 Kelvin - (UL) Universal Voltage 120-277V

**Features HLN**

- Rugged die cast aluminum construction
- IP66 rated for high ingress protection
- Operation temperature -40 C to 60°C
- Hazardous Location Rated  
Class I DIV 2 Groups A, B, C & D  
Class II DIV 2 Groups F & G
- Mounting Options available
- Tempered glass lens
- Power factor : ≥0.95
- Instant on to full brightness
- Corrosion Proof Grade - WF2
- IK Rating - IK08
- Operating temp -40°C- +60°C / -40°F- +140°
- Input voltage 120-277V
- orkable voltage 90-305V
- UL, DLC Premium, RoHS and FCC certification

**Features HLNB**

- Rugged die cast aluminum construction
- IP66 rated for high ingress protection
- Operation temperature -40°C to 55°C
- Hazardous Location Rated  
Class I DIV 2 Groups A, B, C, & D  
Class II DIV 1 Groups E, F, & G  
Class II DIV 2 Group F & G
- UL, DLC premium Certified
- Up to 150 Lm/W
- 7-year warranty

**Applications**

- Oil Refinery
- Steel mill
- Petrochemical plant
- Wastewater treatment
- Manufacturing plant