



Features

- Frosted lens to reduce glare
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy at 135 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 3000K, 4000K, and 5000K color temperatures
- IP65 Rated for wet locations
- Operating temp -40°C - +60°C
-40°F - +140°F
- Dimensions 21.6" x 21.6" x 5.20"
- Field replaceable modular driver
- LM79/80 report and TM21 data available
- Superior heat management yields 60,000 hours life
- 7 year warranty
- 0-10 V DC dimming standard

DLC Premium 4.0 under Nuwave Model number 60546, 61684, 61685, 61131, 61132, 52050 and 61688

- UL, RoHS and FCC certified
- NSF certified-Splash zone/Non-Food zone
- Input voltage 120-277V or 347-480V
- Workable voltage at 90-305V or 312-528V
- Field Replaceable driver

Applications

- Warehouses
- Storage areas
- Food processing plants
- Cold storage
- Convention centers
- Airports
- Healthcare facilities
- Manufacturing plants
- Food Processing
- Agriculture

Available Options

- 6' cord and plug
- Griplock suspension system
- Stainless steel wire guard
- Occupancy sensor/ Daylight harvesting
- Pendant hook

Items Stocked in Illinois Warehouse

Model Number	Reference #	Lumen	CRI	Voltage	Color Temp (K)	Watts	Lm/W	Wattage Equivalent
HB-18L-30K-UL	60546	16,801	>84	120-277V	3000K	136	123	400W HID
HB-18L-40K-UL	52000/61684	18,025	>84	120-277V	4000K	135	133	400W HID
HB-18L-50K-UL	52001/61685	18,704	>84	120-277V	5000K	136	137	400W HID
HBS-24L-40K-UL	61131	27,421	>84	120-277V	4000K	194	140	750W HID
HBS-24L-50K-UL	61132	27,860	>84	120-277V	5000K	194	142	750W HID
HB-28L-40K-UL	52050	29,245	>84	120-277V	4000K	222	131	1000W HID
HB-28L-50K-UL	52051/61688	29,589	>84	120-277V	5000K	220	134	1000W HID

Available in 3000K, 3500K, 4000K, 4500K, 5000K, and 5700K