



Features

- Frosted lens to reduce glare
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy at 142 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 3000K, 4000K, and 5000K color temperatures
- IP65 Rated for wet locations
- Operating temp -40°C - +60°C
-40°F - +140°F
- Dimensions 21.6" x 21.6" x 5.20"
- LM79/80 report available
- TM21 **Reported Values** as listed in DLC QPL
- TM21 **Calculated Values** subject to manufacturer's interpretation and available on request.
- 7 year warranty
- 0-10 V DC dimming standard
- DLC Premium 5.0 under Nuwave except HBS-18L
- UL, RoHS and FCC certified
- NSF certified-Splash zone/Non-Food zone
- Input voltage 120-277V (UL) or 347-480V (UH)
- Field Replaceable driver
- CRI > 84

Applications

- Warehouses
- Storage areas
- Food processing plants
- Cold storage
- Convention centers
- Airports
- Healthcare facilities
- Manufacturing plants
- Food Processing
- Agriculture

Available Options

- 6' cord and plug
- Cable suspension system
- Stainless steel wire guard
- Occupancy sensor/ Daylight harvesting
- Pendant hook

Items Stocked in Illinois Warehouse

| Model Number | Reference # | Lumens | Color Temp (K) | Watts | Lm/W | Wattage Equivalent |
|-------------------|-------------|--------|----------------|-------|------|--------------------|
| HB-18L-30K-UL | 60546 | 16,801 | 3000K | 136 | 123 | 400W HID |
| HB-18L-30K-UL-MW | 61683 | 17,575 | 3000K | 135 | 130 | 400W HID |
| HB-18L-40K-UL-MW | 61684 | 18,029 | 4000K | 135 | 133 | 400W HID |
| HB-18L-40K-UH | 52310 | 18,063 | 4000K | 144 | 125 | 400W HID |
| HB-18L-50K-UL-MW | 61685 | 18,256 | 5000K | 135 | 135 | 400W HID |
| HB-18L-50K-UH | 52311 | 18,120 | 5000K | 146 | 124 | 400W HID |
| HBS-18L-40K-UL | 61111 | 16,525 | 4000K | 137 | 121 | 400W HID |
| HBS-18L-50K-UL | 60474 | 16,834 | 5000K | 137 | 123 | 400W HID |
| HBS-24L-40K-UL | 61131 | 27,421 | 4000K | 195 | 140 | 1000W HID |
| HBS-24L-40K-U, | 61332 | 27,437 | 4000K | 194 | 140 | 1000W HID |
| HBS-24L-50K-UL | 61132 | 27,860 | 5000K | 194 | 142 | 1000W HID |
| HBS-24L-50K-U, | 61333 | 28,201 | 5000K | 194 | 145 | 1000W HID |
| HB-28L-30K-UH | 60419 | 27,692 | 3000K | 217 | 127 | 1000W HID |
| HB-28L-30K-UL- MW | 61686 | 29,199 | 3000K | 222 | 132 | 1000W HID |
| HB-28L-40K-UH | 52410 | 28,676 | 4000K | 232 | 124 | 1000W HID |
| HB-28L-40K-UL | 52050 * | 28,333 | 4000K | 232 | 122 | 1000W HID |
| HB-28L-40K-UL-MW | 61687 | 29,703 | 4000K | 222 | 134 | 1000W HID |
| HB-28L-50K-UH | 52411 | 28,676 | 5000K | 232 | 124 | 1000W HID |
| HB-28L-50K-UL-MW | 61688 | 29,955 | 5000K | 222 | 135 | 1000W HID |

* Replacement to be same Model# with MW suffix

MW = Mean Well Driver

IND = Inventronics Driver