



Features

- Frosted lens to reduce glare
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy at 122-123 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 4000k and 5000k color temperatures
- IP65 Rated for wet locations
- Operating temp -40°C - +60°C
-40°F - +140°F
- Dimensions 21.6" x 21.6" x 5.20

- Superior heat management yields 50,000 hours life
- 0-10 V DC dimming Standard
- UL, DLC, RoHs and FCC certified
- 7 year warranty
- Workable Voltage at 90-305V

Applications

- Indoor/outdoor lighting
- Warehouses
- Storage areas
- Retail stores
- Malls
- Convention centers
- Airports

Ordering Information:

Ex. LB-8L-50KNV-WG



Model

LB

Lumen Package

8L = 8,000 Lm, 64W
11L = 11,000 Lm, 88W

CCT

40K = 4000K
50K = 5000K

Voltage

NV = 120-277v
HV = 347-480v

Options

OS = Occupancy Sensor set
CR = Commissioning Remote (for OS)
WG = Wireguard
AC5 = Aircraft Cable (5ft)
AC10 = Aircraft Cable (10ft)
CD = 6' Cord
PS1 = 120V Straight blade plug
PS2 = 277V Straight blade plug
PT1 = 120V Twist-Lock plug
PT2 = 277V Twist-Lock plug
PH = Pendant Hook