



Features

- Compatible with electronic ballast, magnetic ballasts in AC100-277V
- Work both with or without ballast
- Fits standard T8 / T12 G13 Sockets
- 1.1" max diameter
- 7 year warranty
- 100-277V
- Power factor > 96%
- Instant on - 200 mA current
- ANSI surge protection
- Up to 150 lumens/watt
- CRI >80
- 250° beam angle
- THD <20% +/- 2%
- Lamp Life 60,000 hours
- Available in 3,500, 4,000K and 5,000K
- Standard white finish at ends
- LM-79 LM-80 certified
- Non-dimmable
- Housing: Nano-plastic with full length ridge aluminum structure for heat dissipation
- Safety certifications: UL 1958C
- Operating temp -40°C - + 45°C / -40°F - + 113°F

Applications

- Offices
- Workshops
- Basements
- Task lighting

Opti-fit Gen 2									
A/B	Reference #	New Model Number	Length	Lumens	Watts	Lm/W	CCT	DLC	Voltage
Opti-fit Gen 2	60787	TDT48-2L-40K-UL	4'	2000	18	120	4000	V4.0	120-277V
Opti-fit Gen 2	60788	TDT48-2L-50K-UL	4'	2000	18	120	5000	V4.0	120-277V



Testing Report

